

Presentation for Environmental Testing Instrument



8th March 2025



MES




Trust, only one you can find here.
Amigos
International Co., Ltd.

AGENDA



Water Quality Testing Instruments



Air Quality Monitoring Instruments

What is basic water quality?

➤ Chemical

➤ Physical

➤ Biological





Physical Parameter

- Color
- Taste
- Odor
- Temperature
- Turbidity
- Solid
- Electrical Conductivity



Chemical Parameter

- pH
- ORP
- Acidity
- Alkalinity
- Chlorine
- Hardness
- Dissolved Oxygen
- Biological Oxygen Demand



Biological Parameter

- Bacteria
- Algae
- Viruses

PHYSICAL PARAMETER

Physical parameters are numerical values that describe the size, energy output, and other characteristics of an object or system. These parameters can be used to measure the strength of magnetic fields, temperatures, and densities





Color

Color in water may result from a variety of sources including natural metallic ions (iron and manganese), humus and peat materials, plankton, weeds, and industrial wastes.

True color is measured after a sample of water has been collected and purified (either by centrifuging or filtration). Pure water tends to look cyan in color and a sample can be compared to pure water with a predetermined color standard or comparing the results of a spectrophotometer.



Taste

Taste in water can be caused by foreign matter, such as organic compounds, inorganic salts or dissolved gases. These materials may come from domestic, agricultural or natural sources.



Odor

Musty, Moldy, Earthy, Grassy or Fishy Odor. Although these odors are harmless, the human senses of taste and smell are extremely sensitive even at a very low level. These kinds of odors may be due to: Decaying organic matter in the drain. Pollution of well water from surface drainage.



Turbidity

Turbidity is a measure of water clarity. High turbidity makes the water appear cloudy or muddy. Why do we measure turbidity? Turbidity and total suspended solids (TSS) are different ways to measure similar water quality characteristics.



Temperature

Water temperature is a measure of the kinetic energy of water and is expressed in degrees Fahrenheit (F) or Celsius (C). Water temperature varies according to season, depth, and, in some cases, time of day.



Electrical Conductivity

Electrical conductivity measures the ability of water to conduct an electrical current. The higher the concentration of dissolved charged chemicals (also known as salts) in the water, the greater the electrical current that can be conducted.

CHEMICAL PARAMETER

Chemical parameters include pH, acidity, alkalinity, anions such as chlorides, sulfates fluorides, nitrates, hardness, metals such as iron, manganese, copper, and zinc, BOD, COD, and other toxic inorganic and organic substances. Reactions in living organisms are only possible within a restricted range of pH.





Acidity & Alkalinity

More precisely, acidity and alkalinity are defined as a water's capacity to neutralize strong bases or acids, respectively. The term **“acidic”** for pH values below 7 does not imply that the water has no alkalinity; likewise, the term **“alkaline”** for pH values above 7 does not imply that the water has no acidity.

pH/ORP

pH measures the concentration of hydrogen ions in water, providing a direct measure of how acidic or alkaline the water is. ORP measures the electrical potential needed to transfer electrons among participants in a chemical reaction, indicating the oxidizing or reducing power of the water.



Chlorine

Chlorine is used to remove germs, such as bacteria and viruses, from drinking water, surfaces, swimming pools and spas, sewage, and industrial waste. Chlorine is used to whiten materials such as clothing and paper.



Dissolved Oxygen

Dissolved oxygen (DO) is the amount of oxygen that is present in water. Water bodies receive oxygen from the atmosphere and from aquatic plants. Running water, such as that of a swift moving stream, dissolves more oxygen than the still water of a pond or lake.



Hardness

Water described as **“hard”** contains high amounts of calcium and magnesium, which are naturally found in the Earth's crust. Total hardness is the sum of the calcium and magnesium concentrations, both expressed as calcium carbonate, in milligrams per liter (mg/L)



Biological Oxygen Demand

Biological Oxygen Demand is a measure of the amount of oxygen required to remove waste organic matter from water in the process of decomposition by aerobic bacteria (those bacteria that live only in an environment containing oxygen).




Biological Parameter

Biological parameters of water include: bacteria, algae, viruses, nutrients like phosphate and nitrogen, turbidity, pH, temperature, dissolved oxygen, biological oxygen demand (BOD), and the presence of various aquatic organisms like zooplankton and macroinvertebrates, which indicate the overall health of the water ecosystem.



Algae

Algae are microscopic organisms that live in water and can be found in fresh, salt, and brackish water. While most algae are harmless, some types can produce toxins that can harm people, animals, and the environment.



Bacteria

Bacteria in water can include coliform bacteria, E. coli, Legionella, Salmonella, and Cryptosporidium. Some of these bacteria can cause disease.



Viruses

Viruses can be found in water, and can cause illnesses in humans. The most common viruses in water include adenoviruses, enteroviruses, noroviruses, and hepatitis A and E viruses.

Impacts Water Quality

Key impacts of water quality:

Acidic water: The primary concern is the generation of acidic water due to the exposure of sulfide minerals, leading to low pH levels and the mobilization of heavy metals like lead, copper, and arsenic.

Sedimentation: Mining activities disturb large amounts of soil, causing increased sediment loads in waterways, which can disrupt aquatic ecosystems and impair water clarity.

Chemical contamination: Depending on the minerals being mined, various chemicals used in the extraction process can leach into water sources, including cyanide, mercury, and other toxic substances.

Impacts on aquatic life: Contaminated water from mining can directly harm aquatic organisms by disrupting their physiology and causing reproductive issues.

Drinking water contamination: In areas where mining is prevalent, nearby water sources used for drinking may be contaminated with harmful chemicals, posing a health risk to communities.



Water Quality Monitoring

Water quality monitoring defined by the International Standardization Organization (ISO) as:

“**The** programmed process of sampling, measurement and subsequent recording or signaling, or both, of various water characteristics, often with the aim of assessing conformity to specified **objectives**”.

Three types of monitoring activities-

- long-term
 - short-term
 - continuous
- The long-term, standardized measurement and observation of the aquatic environment in order to define status and trends.
- The short-term, intensive programmes to measure and observe the quality of the aquatic environment for a specific purpose.
- The continuous, specific measurement and observation for the purpose of water quality management and operational activities.



Application



Food and Dairy



Aquaculture



Drinking Water



Wineries



Industrial Process



Wastewater



Swimming Pools



Breweries



Environment



Water Treatment



Boilers & Cooling



Catering



Agri/horticulture



Metal



Educational

Type of Instrument

Chemical Test Kits



Handheld Colorimeters



pH/ISE



Turbidity



Titration



Dissolved Oxygen



Refractometers



Process Instrumentation



Photometers



Mini Controllers



Reagents



Electrodes

Type of Instrument

Single/Multi Tester



Research Grade
Benchtop Meter



Handheld Single
Parameter Meter



Wireless Tester



Handheld
Multiparameter



Thermometer



Chemical Test Kit



Chemical Oxygen
Demand (COD) Set



Spectrophotometer



Mini Controllers



Swimming Pool
pH/ORP Controller



Thermo-Hygrometer

Type of Instrument



Kemio™ Heavy Metals Kit



Lumiso Pooltest Expert



Turbidity Meter



Electrochemical Meters



Wagtech™ Potalab+ Kit



Pool Contour Comparator



Digital Arsenic Test Kit



Type of Instrument



Analyzers



OxiTop® -
Respirometers



Photometers and
Colorimeters



Process Controllers
and Sensors



Germany



Turbidimeters



pH/ORP, Cond, DO
Meters



pH/ORP, Cond, DO
Meters



Type of Instrument



USA

Multi-paramter
Water Quality
Sonde



Wastewater
Process
Monitors and
Sensors

ProDSS
Multiparameter
Digital Water
Quality Meter



Water Level
Logger

Flow Probe



Oil Water
Interface
Meter

Water Level
Sounder





History

The company started in Italy in 1978, and is now located in Woonsocket, RI, USA.

Location

Hanna manufactures over 3,500 products in production facilities located in USA, Romania, Italy and Mauritius.

Philosophy

Our philosophy is to supply customers around the world with practical, cost-effective solutions for their testing needs with world-class service and support.

Development

In 1984 Hanna developed the **world's first micro-** processor based handheld portable pH meter (HI8424) and our innovation continues to this day.

Quality Control

All Hanna products are in compliance with international standards and our production facilities are ISO 9001 :2000 certified.

18
75

Wilkinson and Simpson
formed

19
60

**Dr Palin's method for
DPD** become the
global standard

19
83

Halma plc acquires
Wilkinson and Simpson

19
89

Wilkinson and Simpson
renamed to Palintest

19
92

Palintest starts
operating in Australia

19
93

Palintest starts
operating in USA

20
05

Palintest starts
operating in China

20
11

Palintest acquires
Wagtech

20
13

Palintest wins
**Queen's Award for
International Trade**

20
17

Palintest USA move to
new facility

20
18

Palintest opens
additional UK site

20
19

Palintest releases
Kemio

"Safeguarding water for everyone, every day"



WTW was founded in 1945 and is specialized in development and manufacturing of high quality measurement technology for water analysis.

Product portfolio includes benchtop meters and sensors, continuously operating, stationary measuring systems and portable meters as well as sensors and probes for mobile use.

WTW products are manufactured exclusively in Germany, directly in our Weilheim in Oberbayern site.




The legacy of our global company reaches back to 1948 and a three-man partnership that was forged at Antioch College in Yellow Springs, Ohio, USA. This village, between Dayton and Columbus, still serves as the headquarters for what started as the "Yellow Springs Instrument Company" — now known as YSI Inc.





GPS Multiparameter Meters




- ✓ The HI9829 is a waterproof portable logging multiparameter meter that monitors up to 14 different water quality parameters.
- ✓ The microprocessor based multi-sensor probe allows for the measurement of key parameters including pH, ORP, conductivity, dissolved oxygen, turbidity, ammonium, chloride, nitrate, and temperature.
- ✓ The probe transmits readings digitally with options to log data while disconnected from the meter.
- ✓ An optional GPS provides location tracking of measurements.
- ✓ The complete system is simple to setup and easy to use.
- ✓ The HI9829 is highly customizable and supplied with all necessary accessories, packaged in a durable carrying case.



Research Grade Meter

pH/ORP/ISE and EC/TDS/ Resistivity/Salinity and Temperature



- ✓ HI-5522 is a high grade benchtop instrument that measures measures seven parameters and incorporates dual channels with a separate temperature probe input and support external reference electrodes required by half-cell pH sens
- ✓ pH - Range: -2.0 to 20.0 pH; -2.00 to 20.00; -2.000 to 20.000 pH
- ✓ mV - Range: ± 2000 mV
- ✓ ISE - Range: 1×10^{-6} to 9.99×10^{10} concentration
- ✓ Temperature - Range: -20.0 to 120.0°C
- ✓ EC - Range: 0.000 to 9.999 $\mu\text{S}/\text{cm}$; 10.00 to 99.99 $\mu\text{S}/\text{cm}$; 100.0 to 999.9 $\mu\text{S}/\text{cm}$; 1.000 to 9.999 mS/cm; 10.00 to 99.99 mS/cm; 100.0 to 1000.0 mS/cm
- ✓ TDS - Range: 0.000 to 9.999 ppm; 10.00 to 99.99 ppm; 100.0 to 999.9 ppm; 1.000 to 9.999 ppt; 10.00 to 99.99 ppt; 100.0 to 400.0 ppt
- ✓ Resistivity - Range: 1.0 to 99.9 $\Omega \cdot \text{cm}$; 100 to 999 $\Omega \cdot \text{cm}$; 1.00 to 9.99 $\text{K}\Omega \cdot \text{cm}$; 10.0 to 99.9 $\text{K}\Omega \cdot \text{cm}$; 100 to 999 $\text{K}\Omega \cdot \text{cm}$; 1.00 to 9.99 M $\Omega \cdot \text{cm}$; 10.0 to 100.0 M $\Omega \cdot \text{cm}$
- ✓ Record: 100,000 data point storage
- ✓ Power Supply: 12 VDC adapter

Multiparameter Photometer with COD for Water and Wastewater

- ✓ HI83399 benchtop photometer measures 40 different key water and wastewater quality parameters using 77 different methods that allow for multiple ranges and variations in chemistry for specific applications.
- ✓ Chemical Oxygen Demand (COD) parameter is included for industrial and municipal wastewater treatment.
- ✓ The Phosphorous and Nitrogen parameters included are beneficial to municipal wastewater treatment customers that need to monitor their biological and chemical nutrient removal process.



Alkalinity
Aluminium
Ammonia
Bromine
Calcium
Chloride
Chlorine Dioxide
Chlorine
Chromium (VI)
COD
Colour
Copper
Cyanuric Acid
Fluoride
Hardness, Total

Hydrazine
Iodine
Iron
Langelier Water
Balance Index
Magnesium
Manganese
Molybdenum
Nickel
Nitrate
Nitrite
Nitrogen
Oxygen, Dissolved
Oxygen Scavengers
Ozone

pH-Phenol Red
Phosphate
Phosphorus, Acid
Hydrolyzable
Potassium
Silica
Silver
Sulfate
Surfactants, Anionic
Zinc

40 Parameters

HANNA
instruments



Turbidity Portable Meter



- ✓ The HI98703 is a high accuracy ($\pm 2\%$ of reading plus 0.02 NTU) Turbidity Portable Meter.
- ✓ The applicable range is 0-40 nephelometric turbidity units (NTU)
- ✓ Detector: Centered at 90° to the incident light path and not to exceed $\pm 30^\circ$ from 90° . The detector, and filter system if used, shall have a spectral peak response between 400 nm and 600 nm
- ✓ Data Logging - Up to 200 measurements can be stored
- ✓ Calibration - A two, three, or four-point turbidity calibration
- ✓ Power Supply - 4 x 1.5V AA alkaline batteries or AC adapter



Wagtech™ Potalab+



- ✓ The Potalab+ is the most advanced portable water quality laboratory.
- ✓ With complete digital instrumentation, the Potalab+ delivers laboratory levels of accuracy and is inclusive of digital arsenic testing.
- ✓ The kit is ideally suited to longer-term surveillance and professional monitoring in rural locations.

Tests

- ⌚ **Chemical tests** for ammonia, arsenic, free chlorine, total chlorine, fluoride, nitrate and nitrite
- ⌚ **Physical tests** for turbidity, pH, conductivity, TDS and temperature
- ⌚ **Microbiological tests** for thermotolerant or faecal coliforms and total coliforms



**Produits
Humanitaires et
Wagtech**

Améliorer l'eau potable
et les standards WASH
pour tous

www.palintest.com

Lumiso Expert Robust Multi-parameter Photometer

Features

- ✓ Robust construction - Impact tested to IK08 as part of EN61010. Scratch and chemical resistant coating.
- ✓ IP67 waterproof design - Designed for use in wet and humid environments.
- ✓ Large touchscreen interface - Intuitive and accessible with easy navigation, also works with wet and gloved hands.
- ✓ Multilingual onscreen instructions - Step-by-step instructions on performing tests with little to no prior training required.
- ✓ Data logging - Results are saved automatically, including test data, user, labels, and notes for audit and compliance.
- ✓ Data retrieval - Easy access to data via Palintest Connect.
- ✓ Recycled Materials - Case is made with recycled plastic.
- ✓ Easy results retrieval with Palintest Connect.



LUMISO PHOTOMETER



Lumiso
A Palintest Product



Palintest
Water Analysis Technologies

37 Parameters

Alkalinity
Aluminium
Ammonia
Bromine
Calcium Hardness
Chloride
Chlorine Dioxide
Chlorine
Chromium (VI)
COD
Colour
Copper
Cyanuric Acid
Fluoride
Hardness, Total

Hydrogen Peroxide
HR
Iron
Langelier Water
Balance Index
Magnesium
Manganese
Molybdate
Nickel
Nitrate
Nitrite
Ozone
Phosphate
pH-Phenol Red

Potassium
Salt
Silica
Sulfate
Sulfide
Sulfite
Total Nitrogen
Transmittance
Turbidity
Zinc

Palintest
Water Analysis Technologies



Arsenic Test Kit

The Palintest Arsenator kit solves the complex problem of how to measure Arsenic in the field accurately and safely.

Built around an unique tri-filter assembly, the Palintest Arsenator simplifies and improves field arsenic testing to exceed the **WHO guideline value of 10 ppb in drinking water**.

- Sensitivity down to 2 parts per billion - unique in a field analysis system
- 3-stage filter system increases sensitivity, removes interference from Sulfide and protects the operator.
- Comprehensive field kit containing all required accessories and consumable.

Measuring System Colorimeter

Range 2 – 100 ppb ($\mu\text{g/L As}$)

Display LCD

Reaction time 20 minutes

Size (W x L x H) & 390 x 330 x 95 mm,

Weight 1.75g





Kemio™ Multi



- ✓ Kemio™ uses a sophisticated electrochemical technique, powered by **Palintest's** patented single-use sensor technology, to test for chemicals and heavy metals in water.
- ✓ It is widely used by public authorities, water utilities and water management organisations, and the food and beverage industry to protect the public and the environment and ensure compliance with regulations.
- ✓ **Kemio's** single-use sensors generate an electrical current by reacting with the chemical or metal in the water sample. Kemio™ measures this electrical signal to determine the concentration of contaminants within the sample.

Spectrophotometer photoLab® 7600 UV-VIS

photoLab® 7600 UV-VIS covering the range from 190 to 1100 nm. Ideal for additional self-control with optical reagent-free methods (OptRF) and UV-VIS procedures for many applications.

- Barcode support for test kits in round and rectangular cuvettes
- Automatic cuvette recognition with 10, 20 and 50 mm cuvettes
- Automatic measurement range adjustment
- Automatically stored data and comfortable data management
- More than **200 methods** including special procedures such as free Ammonia, CO₂, SAC and color
- Programming of user-defined methods
- Eco-friendly minimization of reagents and tests
- Linking IQ Sensor Net to photometric methods



BOD Self Check System



- ✓ BOD Standard Measurement for Self-checking according to DIN EN 1899-2 and ASTM 5210 D
- ✓ Up to 12 parallel samples in a sample set
- ✓ Statistic averaging
- ✓ Measurement duration between 0.5 h and 180 days
- ✓ For special applications: Freely selectable vessel, sample volume and incubation temperature
- ✓ BOD measuring range up to 400000 mg/l - Automatic calculation of dilution as a function of total volume and vessel.

Digital Handheld Water Flow Probe



Records 30 data sets, and readings are in feet or meters per second.



Telescoping handles ranging from 3 feet to 14 feet



Rain-proof digital computer and display with 5 year shelf life



Lightweight, rugged and reliable



EXO MULTIPARAMETER SONDES

1. Conductivity/Temperature,
2. Depth,
3. Dissolved Oxygen,
4. fDOM,
5. ISE
6. Ammonium,
7. ISE Chloride,
8. ISE Nitrate,
9. pH,
10. pH/ORP,
11. Rhodamine,
12. Total Algae (PC or PE),
13. Turbidity,
14. UV Nitrate



PRODSS MULTIPARAMETER DIGITAL WATER QUALITY METER

Parameters

Dissolved Oxygen (optical)

Turbidity

Total Algae-Phycocyanin

Total Algae-Phycoerythrin

pH

ORP/Redox

Conductivity

Specific Conductance

Salinity

Total Dissolved Solids (TDS)

21

Resistivity

Seawater Density

Total Suspended Solids (TSS)

Depth

GPS Coordinates

Ammonium

Ammonia

Chloride

Nitrate

Temperature

Barometric Pressure



a xylem brand



WHAT IS THE BASIC OF AIR POLLUTION?

📌 Chemical

📌 Physical

📌 Biological

Indoor

Out
door

Chemical Parameter


- Air Quality Index (AQI),
- Carbon Monoxide (CO),
- Nitrogen Monoxide (NO),
- Nitrogen Dioxide (NO₂),
- Ozone (O₃), Sulphur
- Dioxide (SO₂),
- Ammonia (NH₃),
- Particulate matter (PM₁₀ & PM_{2.5})
- Etc.

Physical Parameter

- Air temperature
- Relative humidity
- Air movement
- Wind Speed & Direction
- Ultraviolet (UV)
- Etc.

Biological Parameter


- Bacteria,
- Molds,
- Mildew,
- Viruses,
- Animal Dander and
- Cat saliva,
- House dust,
- Mites,
- Cockroaches, and
- Pollen
- Etc.



Chemical Parameter

The primary chemical parameters used to measure air quality and assess its impact on health are particulate matter (PM), specifically PM_{2.5}, and various gases like ozone, sulfur dioxide, nitrogen dioxide, and carbon monoxide.






Air Quality Index (AQI),


The Air Quality Index (AQI) is used for reporting daily air quality. It tells you how clean or polluted your air is, and what associated health effects might be a concern for you. The AQI focuses on health effects you may experience within a few hours or days after breathing polluted air.

COMPOSITION OF AIR



Particulate Matter (PM)

PM stands for particulate matter (also called particle pollution): the term for a mixture of solid particles and liquid droplets found in the air. Some particles, such as dust, dirt, soot, or smoke, are large or dark enough to be seen with the naked eye.



Gases

More than 99% of air is made of three gases: nitrogen, oxygen, and argon. Air contains other gases in very small quantities, including gaseous water, which is called water vapor. Air also contains solids and liquids.

Physical Parameter

Physical parameters in air refer to measurable characteristics that describe the state and behavior of air, including temperature, pressure, density, humidity, and the presence of various gases and particles. These parameters are crucial for understanding atmospheric conditions, air quality, and weather patterns.





Relative Humidity

Air relative humidity is a measure of the amount of moisture in the air compared to the maximum amount of moisture the air can hold at that specific temperature.




Temperature

Air temperature refers to the degree of hotness or coldness of the surrounding air, essentially measuring how warm or cool the air is at a given location, typically measured in degrees Celsius (°C) or Fahrenheit (°F).



Winds

Wind is the movement of air, and it can be gentle or strong. It's caused by differences in air pressure, which are created by temperature differences.



Biological Parameter

Biological parameters in air are biological contaminants, such as bacteria, viruses, and pollen, that can be found in both indoor and outdoor air.



Viruses

A virus is a submicroscopic infectious agent that replicates only inside the living cells of an organism. Viruses infect all life forms, from animals and plants to microorganisms, including bacteria and archaea. Viruses are found in almost every ecosystem on Earth and are the most numerous type of biological entity.




Mold



Mildew


Bacteria

Bacteria are tiny, single-celled living organisms. There are millions of different types of bacteria. Many can be found in and on your body and are beneficial to you.



Mold and Mildew

Mold and mildew are both types of fungi that grow in damp environments. Mold can be fuzzy and come in many colors, while mildew can be powdery and appear flat.



Air Pollution



Pollutants can be either:

- Primary Pollutants: emitted directly to atmosphere
- Secondary Pollutants: formed by reactions involving primary pollutants and other constituents within the atmosphere

Sources can be either:

- Stationary: Chimneys, lagoons, refineries, etc
- Mobile: Automobile, ships, planes, etc

Cause of source can be:

Natural - **decomposing organics, wildfire, volcano, dust storm,...**

Anthropogenic - burning of fossil fuels for electrical energy generation, automobile transportation, industry, ...

Urban - motor vehicle

Pollutants of Interest



USEPA Reference Pollutants

Air Pollutant of interest	Type	Source Example	Useful Detection Limits	Range to Expect	Level
Ozone (O3)	Secondary	Formed via UV (sunlight) and pressure of other key pollutants	10 ppb	0-150 ppb	75 ppb (8 hr)
Carbon monoxide (CO)	Primary	Fuel combustion- mobile sources, industrial processes	01 ppm	0-0.3 ppm	9 ppm (8 hr) 35 ppm (1 hr)
Sulfur Dioxide (SO2)	Primary	Fuel combustion- mobile sources, industrial processes	10 ppb	0-100 ppb	75 ppb (1 hr) 0.5 ppm (3 hr)
Nitrogen Dioxide (NO2)	Primary and Secondary	Fuel combustion-mobile sources, electric utilities, off-road equipment	10 ppb	0-50 ppb	100 ppb (1 hr) 53 ppb (1 yr)
Carbon Dioxide (CO2)	Primary	Fuel combustion-electric utilities, mobile sources	100 ppm	35-600 ppm	None
Fine particulate matter (PM2.5)	Primary and Secondary	Fuel combustion (mobile sources, electric utilities, industrial processes), dust, agriculture, fires	5 µg/m3 (24-hr)	0-40 µg/m3 (24-hr)	35 µg/m3 (24-hr) 12 µg/m3 (1 yr)
Particulate matter (PM10)	Primary and Secondary	Dust, fuel combustion (mobile sources, industrial processes), agriculture, fires	10 µg/m3 (24-hr)	0-100 µg/m3 (24-hr)	150 µg/m3 (24 hr)

Hazardous and Odorous Pollutants


Compound	Type	Issue	Sources	Detection required
VOC	Primary	Health Odour	Industries, urban	<1 ppb
H ₂ S	Primary	Odour Health at high levels	Industries, WWTP	1 ppb Odour 1 ppm Health
N ₂ O	Primary	GHG	Natural Anthropogenic Urban WWTP	1 ppm
Methane	Primary	GHG Health (LEL)	Natural Agriculture Landfill	10 ppm 1% LEL

What is Aerosol

Aerosol :
Fume, Mist, Smoke, Dust



Particle Sizes



← Environmental / Naturally Occurring Particles →


← Workplace / man-made Particles →



Size Matters!

Respiratory Tract

- Extrathoracic region: uppermost region
- Tracheobronchial (TB) region: middle region
- Alveolar (A) region: innermost region




Based on International Commission of Radiological Protection (1994) and U.S. Environmental Protection Agency (1996a).

Air Quality Criteria for Particulate matter, 2004, p 6-5.

Sources of Gas



Atmospheric Testing




METHANE (lighter than air)

CARBON MONOXIDE (slightly lighter than air)

HYDROGEN SULFIDE (heavier than air)

Normal Atmosphere

■ Oxygen ■ Nitrogen ■ Other



A diamond-shaped hazard label with a yellow border and a teal center. The word "OXYGEN" is written in bold, dark red, sans-serif capital letters in the center.

OXYGEN

Oxygen
Deficiency




Oxygen Deficiency

Risk of asphyxiation Caused by


- ◆ Consumption
- ◆ People
- ◆ Oxidation
- ◆ Bacterial action
- ◆ Displacement
 - ◆ Humidity
 - ◆ Inert gases

Accident VDO



Oxygen Enrichment

- Serious fire hazard
Materials burn much more rapidly
- Caused by
 - leaking valves
 - leaking cylinders



Accident VDO

Effects of Oxygen

23.5% vol.

- Maximum safe level (OSHA)

21.0% vol.

- Oxygen content in Air (20.954%)

19.5% vol.

- Minimum safe level (OSHA, NIOSH)

17.0% vol.

- Impairment of judgment begins

16.0-12.0% vol.

- Breathing and pulse rate increase, coordination is impaired

Effects of Oxygen

14.0-10.0% vol.

- Fatigue, disturbed respiration

10.0-6.0% vol.

- Nausea and vomiting, inability to move freely and loss of consciousness

<6.0 % vol.

- Convulsive movements and gasping respiration occurs; later heart rate ceases

3.0-5.0% vol.

- Life expectancy three to five minutes

Carbon Monoxide Data

- CO: Colorless, odorless, byproduct of incomplete combustion
- Hazard: Flammable, LEL 12.5%
- Health: Very Toxic (can be absorbed 200-300 time faster than oxygen by the hemoglobin)
- Industries : Steel mills, garages, general industries



Effects of CO

50 ppm

- Permissible exposure limit, 8 hour OSHA

400 ppm

- Frontal Headache in 2-3 hours

1600 ppm

- Headache and nausea 20 minutes
- Collapse and death in 1-2 hours

6400 ppm

- Headache, dizziness in 1-2 minutes, unconsciousness and death in 10-15 minutes

Effects of CO

- Will remain in the body for up to 36 hours.
- The average person exposed to 400 ppm, after 15 minutes, will experience the symptoms of Carbon Monoxide poisoning.

Hydrogen Sulfide Data

- H_2S : Colorless, Rotten egg smell
- Hazard: Flammable, LEL 4.0%
- Health: Extremely Toxic, appears naturally from decomposition, has a paralyzing effect on the nervous system that controls breathing
- Industries : Oil and Gas, pulp and paper, waste water treatment



Effects of H₂S

0.13 ppm

- Minimal perceptible odor

10.0 ppm

- Beginning of eye irritation, permissible exposure limit OSHA


100.0 ppm

- Coughing, eye irritation, loss of sense of smell after two to five minutes


500.0 ppm

- Loss of consciousness and possible death 30 minutes to one hour

Death By Industry



Death By Type of Confined Spaces



Why do we Need to Conduct Air Quality Monitoring?



- **Nuisance:** dust, odour, visible smog
- Protect against hazardous substances
- Understand time and location changes to pollutants in the air
- Discover critical episodes in an industrial plant
- Determine efficiency of pollution control strategies
- Enforce air Quality Regulation

Application



Landfill & Compost



Pulp & Paper



Wastewater



Food & Beverage



Lab. & Research



General Manufacturing



Livestock & Agriculture



Cannabis



Oil & Gas



Mining

APPLICATION

Hot Work




Turnarounds and Shutdowns



Lone Workers



In-Plant Monitoring



Fence-Line and
Perimeter
Monitoring




Confined Spaces




Emergency
Response



Fleet
Management



Personal
Monitoring



Type of Gas



Ammonia (NH_3) Gas Detectors



Chlorine Dioxide (ClO_2) Gas Detectors



Hydrogen Chloride (HCl) Gas Detectors



Carbon Dioxide (CO_2) Gas Detectors



Hydrogen (H_2) Gas Detectors



Hydrogen Cyanide (HCN) Gas Detectors



Carbon Monoxide (CO) Gas Detectors



Chlorine (Cl_2) Gas Detectors



Methane (CH_4) Gas Detectors

Type of Gas



Hydrogen Sulfide
(H₂S) Gas Detectors



Sulfur Dioxide
(SO₂) Gas Detectors



Nitric Oxide (NO)
Gas Detectors



Nitrogen Dioxide
(NO₂) Gas
Detectors



Oxygen (O₂) Gas
Detectors



Phosphine Gas
Detectors (PH₃)

Type of Instruments

SCENTINAL



This continuous monitoring station collects data from a variety of sensors and presents it in an easy to understand graphical interface.

FLYING LAB



Can be used to sample and analyze ambient air at heights of up to 125 meters above ground level.

DR2000



We've improved upon the DR1000 in several ways. [Click here](#) to find out all of the amazing features it now offers.

POLLUTRACKER



Multi-sensor device that measures the concentrations of chemicals using up to 10 sensors and analyzers.

Type of Instruments

HVAC WARDEN



Keeps facility occupants safe by providing real-time air monitoring based on high accuracy detection of dangerous gases.

CTAIR PLUS



This station collects information from a variety of sensors within an urban area and presents it in an easy to understand graphical interface.

AQSAFE



Observes your indoor air quality with up to 12 sensor varieties including temperature and humidity. Sensors can track dust, VOC's, and more.

URBAN SCANNER



A complete scanner solution that provides detailed air quality information within urban landscapes.

Type of Instruments

VENTIS® PRO5

The Ventis Pro5 5-gas monitor gives you the power to monitor up to five gases simultaneously.



VENTIS® MX4

4-Gas Monitor



RADIUS® BZ1

Area Monitor



MX6 IBRID®

Six-Gas Monitor



TANGO® TX2

Two-Gas Monitor



TANGO® TX1

Single-Gas Detector



T40 II RATTLER™

Portable Single Gas Monitor and T-Dock™



GASBADGE® PRO

Single-Gas Monitor



Type of Instruments



Wireless Weather
Station



Wireless Rain
Station




Wireless Plant
Growth Station



Soil Moisture
Meter



Soil Moisture
Meter




Soil Compaction
Tester



Soil Compaction
Tester



Quantum (PAR)
Meter




Light Meter



Soil Moisture
Sensor

- Scentroid is the word leader in air pollution and odour measurement equipment and services.
- Based in Toronto, Canada, we export to over 45 countries around the world.
- We are the **world's** premier manufacturer of odour sampling and analysis equipment.
- With decades of experience developing state-of-the-art instrumentation for environment, nuclear, and medical industries, we bring new and innovative technologies to the field of odour measurement.
- Our clients include government agencies, environmental laboratories, research institutions, and industries dealing with odour nuisances.



1876

Industrial Scientific was born as the research division of the National Mine Service Company (NMS), focused on developing instrumentation to detect methane gas.

**INDUSTRIAL
SCIENTIFIC**



1985

NMS sold the division, and Industrial Scientific Corporation began operating as a private company. With ongoing investments in research and engineering, the gas detector family grew to include patented technologies and state-of-the-art designs.

2017

Industrial Scientific was acquired by Fortive Corporation, a diverse global science and technology company dedicated to accelerating progress around the world. Fortive has and will continue to provide the tools and resources to achieve Our Vision.

2019

Fortive Corporation acquired Intellex Technologies, which develops web-based management systems that optimize business performance, enable regulatory compliance, and streamline ISO initiatives. Paired together, Industrial Scientific and Intellex are a market leader in hardware-enabled software workflows.

Today

We are a leader in lifesaving products and technologies that improve in-the-moment safety outcomes for workers worldwide. Our wearable, area monitoring, and software solutions detect gases, offer remote real-time monitoring, guide emergency response teams, and so much more. Our company has over 1,300 employees across the globe committed to preserving human life and ending death on the job by 2050.



Helping our valued partners transform plant measurements into more profitable growing decisions

**37 YEARS
IN BUSINESS!**

Spectrum[®]
Technologies, Inc.



At Spectrum Technologies, we pride ourselves on helping our valued partners transform plant measurements into more profitable growing decisions. Since 1987, we have manufactured and distributed affordable, leading-edge plant measurement technology to agricultural, horticultural, greenhouse and turf markets globally, serving more than 14,000 customers in 80+ countries.

Air Quality & Odour Monitoring Station

SL50 Scentinal

Maximum # of Sensors	: 20
Type of Sensors	: PID, NDIR, EC, Laser Particulate counter, and MOS
Sampling rate	: 1 per minute
# Of Sampling Ports	: 1 to 2
Weight	: 81 lbs
Size	: 24'' x 20'' x 8''
Power Requirements	: 100-240V 50/60Hz 2A
Power Consumption	: 30W without AC - 150W with AC
Communication	: 3G/4G (default), LAN (default), WIFI (optional), MODBUS
On-board data Storage	: 64GB - SD Card
Cloud Server	: Included by Default
On-Board Server	: Included by Default
User Interface	: 7" touch screen on Panel door and Remote access Sensor Information Management System
Ambient Temperature Range	: 0 to 35 °C without AC system -50 to +50 °C with Heating and AC system
Sample Conditions	: -50 to +50°C and 10 - 90% RH without predilution system -50 to 120°C and 0 - 100% RH with pre-dilution system
Calibration	: Manual, using calibration gas and on-board screen, Optional, automatic calibration using built-in calibration gas
Warranty	: 24 months full warranty on all parts including sensors
Sensor Replacement	: dependent - first 2 years covered by warranty
Sensor Frequency	
Software	: SIMS3 - Sensor Information management System - free access for life of product
Cabinet	: NEMA 4X
Mounting Hardware	: Wall mounting hardware included



SCENTROID
Future of Sensory Technology



CTair Air Quality Monitor

Maximum # of sensors	: 11 (4xEC, 1xC02, 1xPID, 1xCH4, 1xPM, T, RH, Barometer)
Type of sensors	: PID, NDIR, EC, Laser Particulate Counter, Temperature and Humidity, and Barometric Pressure
Relative	
Sampling rate	: Approximately 1/m
Weight	: 4.5kg with solar panel
Size	: 19 x 29 x 14cm CTair unit, 37 x 34cm for solar panel mounted on top
LED Indicator	: Color-changing LED Light displaying unit status
Communication	: WiFi, 3G, 4G, LoRa
Power Requirement	: Solar power and AC power, 110 - 240 VAC
Cloud server	: Data logging, analysis, alarms, remote management
Alarm Equipped	: On cloud, not on the unit itself
Temperature range	: -40 to 40 °C
Operating R. Humidity	: 10 - 90%
Device Health	: Daily sensor health checks and provides sensor replacement reminders
Warranty	: 24 months full warranty to all parts including sensors
Sensor replacement	: Sensor dependent - first 2 years covered by warranty
Mounting	: Configurable for wall or pole mount
Battery Only Runtime	: 36 hours (base model)
Traffic Information	: Vision-based traffic classification and count
Design Rating	: IP53
Local Storage	: SD card - long term continuous logging
Internal Access	: Securable by cable/pad lock
Calibration	: Factory calibration to fully documented procedures in accordance with our ISO 9001 quality management system



Sensors

- Carbon Monoxide
- Chlorine
- Hydrogen
- Hydrogen Chloride
- Hydrogen Cyanide
- Phosphine
- Hydrogen Sulfide
- Nitric Oxide
- Nitrogen Dioxide
- Oxygen
- Sulfur Dioxide
- Formaldehyde
- Non-Methane Hydrocarbon
- Ammonia
- Ozone
- Methanol and Ethanol
- Chlorine Dioxide
- Ethylene

Sensors

- Methyl Mercaptan
- Carbon Disulfide
- Tert Butylthiol
- Tetrahydrothiophene
- Benzene, Toluene, Ethylbenzene, Xylene
- Phosgene
- Dimethyl Sulfide
- Electromagnetic Field
- Radiation Monitor
- Particulate Matter, PM 1, 2.5, 4, 10
- Helium
- Carbon Dioxide
- Methane
- Nitrous Oxide
- Total Volatile Organic Compounds
- Radon Gas
- Benzene
- Methane



RADIUS® BZ1 AREA MONITOR

SENSORS	: Up to 6 sensors (catalytic bead, photoionization detector, electrochemical, IR, and PID) Up to 7 simultaneous readings
WARRANTY	: Two-year warranty, including sensors and battery
KEYPAD	: Three buttons
DATA LOG	: At least 3 months at 10-second intervals
EVENT LOGGING	: 60 alarm events
INGRESS PROTECTION	: IP66
CASE MATERIAL	: Impact-resistant polycarbonate alloys
DIMENSIONS	: 29 x 29 x 55 cm (11.5 x 11.5 x 21.5 in)
WEIGHT	: 7.5 kg (16.5 lb)
TEMPERATURE RANGE	: -20 °C to 55 °C (-4 °F to 131 °F)
HUMIDITY RANGE	: 15% to 95% non-condensing (continuous)
DISPLAY/READOUT	: 11.2 cm (4.4 in) monochrome backlit graphical Liquid Crystal Display (LCD)
POWER SOURCE/RUN TIME	: Rechargeable nickel-metal hydride (NiMH) battery 7 days (168 hours) typical @ 20 °C, without Pump, with Wireless 3.5 days (84 hours) typical @ 20 °C, with Pump, with Wireless only, 30 days (720 hours) typical @ 20 °C, electrochemical sensors without Pump, with Wireless ≤8 hour recharge time
ALARMS	: 108 decibel (dB) at 1 m (3.3 ft) redundant audible alarms Redundant, visual alarm LEDs (red and blue)



**INDUSTRIAL
SCIENTIFIC**

Sensors

Combustible Gases

Ammonia (NH₃):

Carbon Monoxide (CO):

Chlorine (Cl₂):

Hydrogen (H₂):

Hydrogen Sulfide (H₂S):

Hydrogen Cyanide (HCN):

Nitrogen Dioxide (NO₂):

Oxygen (O₂):

Sulfur Dioxide (SO₂):

Phosphine (PH₃):

Nitric Oxide (NO):

Carbon Dioxide (CO₂):

Volatile Organic Compounds(VOCs)




VENTIS® PRO5 MULTI-GAS MONITOR



**INDUSTRIAL
SCIENTIFIC**

SENSORS	: Combustible Gases/Methane - Catalytic Bead O ₂ , CO, CO/H ₂ low, H ₂ S, HCN, NH ₃ , NO ₂ , PH ₃ , Cl ₂ - Electrochemical, CO ₂ , CH ₄ , CO ₂ /LEL, HC - Infrared
SO ₂ , CO ₂ /CH ₄ ,	
KEYPAD	: Two buttons for operation. Dedicated panic button.
DATA LOG	: At least 3 months at 10-second intervals
EVENT LOGGING	: 60 alarm events
INGRESS PROTECTION	: IP68 (submersion at 1.5 meters for 1 hour)
CASE MATERIAL	: Polycarbonate with protective rubber overmold
DIMENSIONS	: 104 x 58 x 36 mm (4.1 x 2.3 x 1.4 in) without Pump 172 x 67 x 65 mm (6.8 x 2.6 x 2.6 in) with Pump 104 x 58 x 61 mm (4.1 x 2.3 x 2.4 in) with wi-fi
Battery	
WEIGHT	: 200 g (7.05 oz) typical, without Pump 390 g (13.76 oz) typical, with Pump 243 g (8.5 oz) typical, with wi-fi Battery
HUMIDITY RANGE	: 15% to 95% non-condensing (continuous)
TEMPERATURE RANGE	: -40 °C to 50 °C (-40 °F to 122 °F) **
DISPLAY/READOUT	: Backlit liquid crystal display (LCD)

Wireless Weather Station




Value	Range	Accuracy
Air Temperature	-40°F to 257°F (-40°C to 125°C)	±0.54°F (-40°F to 194°F) ±0.3 °C (-40°C to 95°C)
Relative Humidity	0 to 100%	±2% @ 77°F (25°C)
Rainfall	0.001" (0.254mm) resolution	±2% at <2" (5cm)/hour
Wind Speed	0.1 to 200mph (0, 1 to 322 km/h)	±2mph (±3km/h) ±5%
Wind Direction	0° -359°, 1° increments	±3°
External Sensor Ports	6x2.5mm Stereo Jack (0to 3.0 VDC Analog Input)	
Operating Temperature	-22°F to 130°F (-30°C to 55°C)	
External Communication	Cellular, WiFi, Radio, Data Logger	
Power Source	3.5W Solar Panel, Rechargeable 6V/4.5AH SLA Battery	
Battery Life	14 Days Minimum Without Solar Power	
Data Capacity	312 Days at 15minute Intervals (30,000 Records)	
Dimensions	12"H x 19.5"L x 11.25"W (30.5cm x 49.5cm x 28.6cm) Add up to 7.25 (18.4cm) Depending on Antenna Used	

Our Services




www.amigosmyanmar.com



[www.facebook.com/](https://www.facebook.com/AmigosInternationalCoLtd)

Amigos International Co., Ltd





Head office Yangon



Branch office
Mandalay



Branch office
Naypyidaw

Contact Us

YANGON HEAD OFFICE

📍 Address: SH-B5(4), Malikha Housing, Yadanar Road, 14 Ward, Thingangyun Tsp, Yangon, Myanmar

☎ Phone: 01 - 3566717, 3560135, 3569732

☎ 09-443087709, 09-400980820, 09 - 5025972, 09 - 786029954, 09 - 786029950

✉ Email: management@amigosmyanmar.com

MANDALAY BRANCH OFFICE

📍 Building No: A-2, Shwe Nan Taw Housing (1), 18st x 19st, Between 58st x 59st, Nan Shae, Aung Myae Thar Zan Tsp, Mandalay.

☎ Phone : 09 - 261995039, 09 - 250678506, 09-400980826

✉ Email : amigos.mdy@gmail.com

NAYPYITAW BRANCH OFFICE


📍 No. Pa/213, Tha Pyay Kone Market Street, Naypyidaw.

☎ 09 - 421169397, 09 - 797991733, 067-3432535

✉ Email : amigos.nptl@gmail.com



Questions



Thank You